



Fuse-link, high speed, 1000 A, AC 1250 V, size 3, 76 x 90 x 139 mm, aR, DIN, IEC, single indicator

Catalog No. 170M6148

Similar to illustration

### Delivery program

|                              |   |    |   |
|------------------------------|---|----|---|
| Product range                |   |    | Fuse  |
| Basic function               |   |    | Fuse-link                                     |
| Field of application         |   |    | high speed                                    |
| Rated current                | I | A  | 1000  |
| Rated voltage                |   |    | AC 1250 V                                     |
| Construction size            |   |    | size 3  |
| Size                         |   |    | 76 x 90 x 139 mm                              |
| Utilization category         |   |    | aR  |
| Status indicator             |   |    | single indicator                              |
| Breaking Capacity            |   | kA | 100   |
| usable for size/applications |   |    | semiconductor protection                      |
| Standard/Approval            |   |    | DIN<br>IEC                                    |
| Shape                        |   |    | square body with centre-bolted tags (slotted) |
| Standards/Regulations        |   |    | DIN 43653<br>IEC 60269-4                      |

### Technical data ETIM 7.0

|   |  |    |   |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |   |
| Construction size   |  |    | Other                                     |
| Rated current   |  | A  | 1000                                      |
| Rated voltage   |  | V  | 1250                                      |
| Voltage type  |  |    | AC  |
| Rated switching capacity  |  | kA | 100                                       |
| Utilization category  |  |    | aR (accompanied semiconductor protection) |
| Type of fuse status indicator   |  |    | Top fuse status indicator                 |
| Insulated metal gripping lugs (IMGL)  |  |    | No  |