



Fuse-link, high speed, 1000 A, AC 690 V, size 3, 76 x 92 x 126 mm, aR, IEC, type K indicator

Catalog No. 170M6364

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1000
Rated voltage			AC 690 V
Construction size			size 3
Size			76 x 92 x 126 mm
Utilization category			aR
Status indicator			single indicator
Description			french style indicator style K for microswitch
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	1000
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No