



Fuse-link, high speed, 40 A, AC 690 V, DIN 000, gR, DIN, IEC, single indicator, live gripping lugs

Catalog No. 170M1413

Delivery program

| | | | |
|------------------------------|---|----|---------------------------------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 40 |
| Rated voltage | | | AC 690 V |
| Construction size | | | DIN 000 |
| Utilization category | | | gR |
| Status indicator | | | single (top) indicator system |
| Description | | | live gripping lugs indicator style T for microswitch |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | DIN IEC |
| Shape | | | square body with offset bolted tags (slotted) |
| Standards/Regulations | | | DIN 43653 IEC 60269-4 |
| Optional accessories | | | fuse-holder 170H1007 |

Technical data ETIM 7.0

| | | | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|-----------------------------------------------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 40 |
| Rated voltage | | V | 690 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 200 |
| Utilization category | | | gR (general purpose semiconductor protection) |
| Type of fuse status indicator | | | Other |
| Insulated metal gripping lugs (IMGL) | | | No |

Additional product information (links)

| | |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| High-speed full-line catalogue (pdf) | http://www1.cooperbussmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|