



Fuse-link, high speed, 315 A, AC 690 V, size 000, 24 x 36 x 96 mm, aR, IEC

Catalog No. 170M1472

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	315
Rated voltage			AC 690 V
Construction size			size 000
Size			24 x 36 x 96 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with offset bolted tags
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	315
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusssmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf
-------------------------	---